# ZSi

### (Industrial Interchange)

One Way Shut-Off - Series 2 thru 6

#### Features:

- · High flow metal valves.
- Precision molded seals form a "bubble tight" seal for reliable operation within rated working pressures. Nitrile (Buna-N) seals are standard. EPDM, Viton and Neoprene seals are available as options.
- Proven ball locking mechanism with large numbers of stainless steel locking balls evenly distribute the load to resist wear and provide positive connections and allow a swiveling action to reduce hose torque.
- Integral sleeve guard protects the sleeve and resists accidental disconnects for the "SG" series.
- Knurling and/or grooves on the sleeve provide a gripping surface for ease of operation.
- Wide range of body sizes, materials, options and end terminations are available to meet specific needs.
- · Accepts Industrial Interchange Plug.



**Operation:** Sleeve type couplings are widely used to connect air and low pressure fluid lines. Their compact and economical design uses a ball locking mechanism consisting of captive stainless steel balls that engage the locking groove on the mating plug. The sliding spring loaded sleeve on the socket must be manually retracted in order to connect or disconnect the plug.

Material: Brass body and socket end, zinc-plated steel sleeve
Working Pressure: 300 PSIG; vacuum to 27" Hg
Interchangeability: Complies with ANSI/NFPA

T3.20.14-1990 & ISO 6150-B

0		Body Size		
Specifications	1/4"	3/8"	1/2"	
Rated Pressure (psig)	300	300	300	
Temp. Range (Buna-N Seal)		-40° to +250° F		
Locking Device	Sta	Stainless Steel Balls		
Vacuum Data (inches Hg)	·			
Disconnected (coupler only)	No	Not Recommended		
Connected	27.4	27.4	27.4	
Approximate CFM at 100 (psi)	37 70 150			

## 2 Series 1/8" Sockets - Foster

		Part No.	FPT	Description
		2302		Brass/Steel
		BL2302		Ball Lock
		2302H		Brass/Steel For Heat, Viton Seal
ead	Female Thread	2302HW	1/8"	Brass/SS For Hot Water, Viton Seal
ٍ €ِ		2302S/S	/8	303 Stainless
E T		BL2302S/S		Ball Lock, 303 Stainless
ema		2302S/SH		303 Stainless For Heat, Viton Seal
ŭ		2302W		Brass/SS For Water, Buna-N Seal
		2702		Brass/Steel
		BL2702		Ball Lock
		2702H	1/4"	Brass/Steel For Heat, Viton Seal
		2702HW		Brass/SS For Hot Water, Viton Seal

		Part No.	MPT	Description
		2202		Brass/Steel
		BL2202		Ball Lock
	40000	2202S/S		303 Stainless
ead	Male Thread	BL2202S/S		Ball Lock, 303 Stainless
e ∏r		2202H	1/8"	For Heat, Viton Seal
Mak		2202S		For Steam, Brass/SS, EPDM Seal
		2202W	For Water, Brass/SS, Buna-N Seal	
		2402		Brass/Steel
		BL2402	1/4"	Ball Lock
		2402H		For Heat, Viton Seal

Brand - Designates F=Foster or B=Breco Part

ZSi-Foster Engineering Catalog

See page 380 for full size templates

- 267 -



# 1/8" One Way Shut-Off - 2 Series

## (Industrial Interchange)

# 2 Series 1/8" Sockets - Foster

		Part No.	I.D.	Description	
		2022		Brass/Steel	
		BL2022	1/8"	Ball Lock	
	- 14 C (12)	2022W	78	For Water, Brass/SS, Buna-N Seal	
E		2032	3/16"	Brass/Steel	
Ste	Hose Stem	BL2032		Ball Lock	
ose		2032HW		For Hot Water, Brass/SS, Viton Seal	
Ť		2032S		For Steam, Brass/SS, EPDM Seal	
		2042		Brass/Steel	
		BL2042	1/4"	Ball Lock	
		2042HW	] ′ •	For Hot Water, Brass/SS, Viton Seal	
	Requires Hose Clamp (See page 200 for typical hose clamps)				

and bing	111	Part No.	Size	Description
	SJ8-2	.170" x ½"	Plastic	
들을	lastic	BLSJ8-2	.170 X /4	Ball Lock, 1/4" Plastic
las etal		SJ8-2M		Soft Metal
₫ ₩	BLSJ8-2M	1/4"	Ball Lock, Soft Metal	
	U	SJ8-2S/S		303 Stainless

Tubing int		Part No.	Size	Description	
율뉱		SJ8P-2		Plastic	
ital Iou	Plastic & Metal Panel Mou	BLSJ8P-2	.170" x ½"	Ball Lock, Plastic	
W We		SJ8P-2HW		Plastic for Hot Water	
		SJ8P-2	SJ8P-2W		Plastic, for Water
last		SJ8P-2M	1/4"	Soft Metal	
₽		BLSJ8P-2M	/4"	Ball Lock, Soft Metal	

## 2 Series 1/8" Plugs - Foster

read	ā	Part No.	FPT	Description
emale Thread		23-2	1/8"	Steel
Fema	23-2 23-2 23-2 23-2	27-2	1/4"	Steel

Male Thread	Part No.	MPT	Description
Ĕ	22-2	1/8"	Steel
<u>е</u>	22-2B	1/8"	Brass
Mal	22-2S/S	1/8"	303 Stainless
_	24-2	1/4"	Steel

_		Part No.	I.D.	Description
Sten		02-2	1/8"	
Hose Stem	17	03-2	<sup>3</sup> /16 <sup>#</sup>	Steel
Ĭ		04-2	1/4"	
	Requires Hose Clamp	(See page 200	for typical ho	se clamps)

bing 🚞	Part No.	Size	Description
	PJ8-2	0.170" x ½"	Plastic
Plastic and Metal Tubing	PJ8-2V	0.170" x 1/4"	Plastic - Valve Core Brass
	PJ8-2VLV	0.170" x <sup>1</sup> / <sub>4</sub> "	Plastic - Less Valve
	PJ8-2M	1/4"	Soft Metal
iti iii	PJ8-2S/S	1/4"	Stainless Steel
Plas	PJ8-2VM	1/4"	Soft Metal - Valve Core Brass

Brand - Designates F=Foster or B=Breco Part - 268 --

See page 380 for full size templates

www.zsi-foster.com

